

HP 1910 Switch Series



Key features

- Customized operation using intuitive Web interface
- Layer 3 static routing with 32 routes for network segmentation and expansion
- Access control lists for granular security control
- Spanning Tree: STP, RSTP, and MSTP
- HP Limited Lifetime warranty 2.0

Product overview

HP 1910 Switch Series consists of advanced smart-managed fixed-configuration Gigabit and Fast Ethernet switches designed for small businesses in an easy-to-administer solution. By utilizing the latest design in silicon technology, this series is one of the most power efficient in the market.

The series has 13 switches: eight Gigabit Ethernet and five Fast Ethernet models. The 8-, 16-, 24-, and 48-port 10/100/1000 models are equipped with additional Gigabit SFP ports for fiber connectivity; in addition to non-PoE models, the 8- and 24-port Gigabit Ethernet models are available with PoE (at two different levels) or without PoE. The 10/100 models are available with 8, 24, and 48 ports, and come with two additional combination uplink ports. The 8- and 24-port Fast Ethernet models are available with or without PoE.

The HP 1910 Switch Series provides a great value, and includes features to satisfy even the most advanced small business network.

All models support rack mounting or desktop operation. Customizable features include basic Layer 2 features like VLANs and link aggregation, as well as advanced features such as Layer 3 static routing, IPv6, ACLs, and Spanning Tree Protocols. The switches come with a limited lifetime warranty covering the unit, fans, and power supplies, as well as 24x7 phone support for the first three years of ownership.

Features and benefits

Management

- Simple Web management

Allows for easy management of the switch—even by nontechnical users—through an intuitive Web GUI; supports HTTP and HTTP Secure (HTTPS)
- Single IP management

Enables management of up to four HP 1910 devices using a single Web interface; simplifies management of multiple devices
- Secure Web GUI

Provides a secure, easy-to-use graphical interface for configuring the module via HTTPS
- SNMPv1, v2c, and v3

Facilitates management of the switch, as the device can be discovered and monitored from an SNMP management station
- Complete session logging

Provides detailed information for problem identification and resolution
- Dual flash images

Provides independent primary and secondary operating system files for backup while upgrading
- Port mirroring

Enables traffic on a port to be simultaneously sent to a network analyzer for monitoring
- Management security

Restricts access to critical configuration commands; offers multiple privilege levels with password protection; ACLs provide telnet and SNMP access; local and remote syslog capabilities allow logging of all access
- Network Time Protocol (NTP)

Synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- IEEE 802.1AB Link Layer Discovery Protocol (LLDP)

Advertises and receives management information from adjacent devices on a network, facilitating easy mapping by network management applications
- Limited CLI

Enables users to quickly deploy and troubleshoot devices in the network
- RMON

Provides advanced monitoring and reporting capabilities for statistics, history, alarms, and events
- Default DHCP client mode

Allows the switch to be directly connected to a network, enabling plug-and-play operation; in the absence of a DHCP server on the network, the switch will fall back to a unique static address determined by the switch's MAC address

Quality of service (QoS)

- Broadcast control

Allows limitation of broadcast traffic rate to cut down on unwanted network broadcast traffic

- Rate limiting

Sets per-port ingress-enforced maximums and per-port, per-queue minimums

- Traffic prioritization

Provides time-sensitive packets (like VoIP and video) with priority over other traffic based on DSCP or IEEE 802.1p classification; packets are mapped to four hardware queues for more effective throughput

Connectivity

- IPv6

- IPv6 host

Enables switches to be managed and deployed at the IPv6 network's edge

- IPv6 routing

Supports IPv6 static routes

- MLD snooping

Forwards IPv6 multicast traffic to the appropriate interface, preventing traffic flooding

- IPv6 ACL and QoS

Supports ACL and QoS for IPv6 network traffic

- Auto-MDI/MDIX

Adjusts automatically for straight-through or crossover cables on all 10/100/1000 ports

- IEEE 802.3x Flow Control

Provides a flow-throttling mechanism propagated through the network to prevent packet loss at a congested node

- IEEE 802.3af Power over Ethernet (PoE) ready

Provides up to 15.4 W per port to power standards-compliant IP phones, wireless LAN access points, Web cameras, and more (for PoE models)

- IEEE 802.3at Power over Ethernet (PoE+)

Provides up to 30 W per port, which allows support of the latest PoE+-capable devices such as IP phones, wireless access points, and security cameras, as well as any IEEE 802.3af compliant end device; reduces the cost of additional electrical cabling and circuits that would otherwise be necessary in IP phone and WLAN deployments (Note: applies to all PoE models, except the two 24G-PoE models, which support a pre-standard implementation of PoE+)

- Packet storm protection

Protects against broadcast, multicast, or unicast storms with user-defined thresholds

- Cable diagnostics

Detects cable issues remotely using a browser-based tool

Security

- Advanced access control lists (ACLs)

Enables network traffic filtering and enhances network control using MAC- and IP-based ACLs; time-based ACLs allow for greater flexibility with managing network access
- Secure Sockets Layer (SSL)

Encrypts all HTTP traffic, allowing secure access to the browser-based management GUI in the switch
- IEEE 802.1X and RADIUS network logins
Controls port-based access for authentication and accountability
- Automatic VLAN assignment
Assigns users automatically to the appropriate VLAN based on their identity, location, and time of day
- STP BPDU port protection
Blocks Bridge Protocol Data Units (BPDUs) on ports that do not require BPDUs, preventing forged BPDU attacks
- STP root guard
Protects the root bridge from malicious attacks or configuration mistakes
- Automatic denial-of-service protection
Monitors for malicious attacks and protects the network by blocking the attacks
- Management password
Provides security so that only authorized access to the Web browser interface is allowed

Performance

- Half- or full-duplex auto-negotiating capability on every port
Doubles the throughput of every port
- Selectable queue configurations
Allows for increased performance by selecting the number of queues and associated memory buffering that best meet the requirements of the network applications
- IGMP snooping
Improves network performance through multicast filtering, instead of flooding traffic to all ports
- Fiber uplink
Provides greater distance connectivity using Gigabit Ethernet fiber uplinks

Layer 2 switching

- VLAN support and tagging
 - Supports IEEE 802.1Q (4,094 VLAN IDs) and 256 VLANs simultaneously
- Spanning Tree Protocol (STP)
 - Supports standard IEEE 802.1D STP, IEEE 802.1w Rapid Spanning Tree Protocol (RSTP) for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)
- BPDU filtering
 - Drops BPDU packets when STP is enabled globally but disabled on a specific port
- Jumbo frame support
 - Supports up to 10-kilobyte frame size to improve the performance of large data transfers

Layer 3 services

- Address Resolution Protocol (ARP)
 - Determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- DHCP relay
 - Simplifies management of DHCP addresses in networks with multiple subnets

Layer 3 routing

- Static IPv4 or IPv6 routing
 - Provides basic routing (supporting up to 32 static routes and eight virtual VLAN interfaces); allows manual routing configuration

Resiliency and high availability

- Available redundant power supply
 - Provides additional PoE of up to 740 W for high-power applications like HP Gigabit Ethernet IntelliJack switches; the HP RPS1600 Redundant Power System (JG136A), which is sold separately, is for use only with the 1910-24G-PoE (365W) switch model
- Link aggregation
 - Groups together multiple ports automatically using Link Aggregation Control Protocol (LACP), or manually, to form an ultra-high-bandwidth connection to the network backbone; helps prevent traffic bottlenecks

Convergence

- LLDP-MED (Media Endpoint Discovery)

Defines a standard extension of LLDP that stores values for parameters such as QoS and VLAN to automatically configure network devices such as IP phones

- PoE allocations

Supports multiple methods (automatic, IEEE 802.3af class, LLDP-MED, or user-specified) to allocate PoE power for more efficient energy savings

- Auto voice VLAN

Recognizes IP phones and automatically assigns voice traffic to dedicated VLAN for IP phones

Additional information

- Green initiative support

Provides support for RoHS and WEEE regulations

- Green IT and power

Improves energy efficiency through the use of the latest advances in silicon development; shuts off unused ports and utilizes variable-speed fans, reducing energy costs

Warranty and support

- HP Lifetime Warranty 2.0

Advance hardware replacement for as long as you own the product with next-business-day delivery (available in most countries). See hp.com/networking/warrantysummary for duration details.

- Electronic and telephone support (for Lifetime Warranty 2.0)

Limited 24x7 telephone support is available from HP for the first three years; limited electronic and business hours telephone support is available from HP for the entire warranty period; to reach our support centers, refer to hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to hp.com/networking/warrantysummary.

HP 1910 Switch Series

Specifications



| | HP 1910-48G Switch (JE009A) | HP 1910-24G-PoE (365W) Switch (JE007A) | HP 1910-24G-PoE (170W) Switch (JE008A) |
|---|---|---|---|
| I/O ports and slots | 48 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 48 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination | 24 RJ-45 auto-negotiating 10/100/1000 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination | 24 RJ-45 auto-negotiating 10/100/1000 PoE ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE) 4 SFP 1000 Mbps ports 1 RJ-45 console port to access limited CLI port Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination |
| Physical characteristics | | | |
| Dimensions | 17.4(w) x 10.24(d) x 1.7(h) in. (44.2 x 26.01 x 4.32 cm) (1U height) | 17.4(w) x 16.54(d) x 1.7(h) in. (44.2 x 42.01 x 4.32 cm) (1U height) | 17.4(w) x 16.54(d) x 1.7(h) in. (44.2 x 42.01 x 4.32 cm) (1U height) |
| Weight | 6.8 lb (3.08 kg) | 6.8 lb (3.08 kg) | 6.8 lb (3.08 kg) |
| Memory and processor | ARM® @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) |
| Performance | | | |
| 100 Mb Latency | < 5 µs | < 5 µs | < 5 µs |
| 1000 Mb Latency | < 5 µs | < 5 µs | < 5 µs |
| Throughput | up to 77.4 Mpps (64-byte packets) | up to 41.7 Mpps (64-byte packets) | up to 41.7 Mpps (64-byte packets) |
| Routing/Switching capacity | 104 Gbps | 56 Gbps | 56 Gbps |
| Routing table size | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) |
| MAC address table size | 8192 entries | 8192 entries | 8192 entries |
| Environment | | | |
| Operating temperature | 32°F to 113°F (0°C to 45°C) | 32°F to 113°F (0°C to 45°C) | 32°F to 113°F (0°C to 45°C) |
| Operating relative humidity | 10% to 90%, noncondensing | 10% to 90%, noncondensing | 10% to 90%, noncondensing |
| Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) |
| Non-operating/Storage relative humidity | 10% to 95%, noncondensing | 10% to 95%, noncondensing | 10% to 95%, noncondensing |
| Acoustic | Pressure: 50.0 dB; ISO 7779 | Pressure: 44.4 dB; ISO 7779 | Pressure: 44.4 dB; ISO 7779 |

| | HP 1910-48G Switch (JE009A) | HP 1910-24G-PoE (365W) Switch (JE007A) | HP 1910-24G-PoE (170W) Switch (JE008A) |
|-----------------------------------|---|---|--|
| Electrical characteristics | | | |
| Frequency | 50/60 Hz Achieved Miercom Certified Green Award | 50/60 Hz | 50/60 Hz |
| AC voltage | 100–240 VAC | 100–240 VAC | 100–240 VAC |
| Maximum power rating | 59.8 W | 523 W | 255 W |
| PoE power | | 365 W | 170 W |
| Notes | | | |
| | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies. |
| Safety | | | |
| | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 |
| Emissions | | | |
| | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Management | | | |
| | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB |
| Notes | | | |
| | SFP ports and copper ports work simultaneously, independent of each other, to provide a total of 52 Gigabit Ethernet-capable ports. | SFP ports and copper ports can work simultaneously, independent of each other, to provide a total of 28 Gigabit Ethernet-capable ports. | SFP ports and copper ports work simultaneously, independent of each other, to provide a total of 28 Gigabit Ethernet-capable ports. |

| | HP 1910-48G Switch (JE009A) | HP 1910-24G-PoE (365W) Switch (JE007A) | HP 1910-24G-PoE (170W) Switch (JE008A) |
|-----------------|---|--|---|
| Services | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 24x7 SW phone support, software updates (UV791E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW491E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW492E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW493E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>Installation with minimum configuration, system-based pricing (UW451E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 24x7 SW phone support, software updates (UV791E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW491E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW492E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW493E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 24x7 SW phone support, software updates (UV791E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW491E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW492E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW493E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> |

HP 1910 Switch Series

Specifications (continued)



| | HP 1910-24G Switch (JE006A) | HP 1910-16G Switch (JE005A) | HP 1910-8G Switch (JG348A) |
|---|--|--|---|
| I/O ports and slots | <p>24 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>4 SFP 1000 Mbps ports</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 24 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination</p> | <p>16 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>4 SFP 1000 Mbps ports</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 16 autosensing 10/100/1000 ports plus 4 1000BASE-X SFP ports, or a combination</p> | <p>8 RJ-45 auto-negotiating 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T)</p> <p>1 SFP 1000 Mbps port</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination</p> |
| Physical characteristics | | | |
| Dimensions | 17.4(w) x 6.3(d) x 1.7(h) in. (44.2 x 16 x 4.32 cm) (1U height) | 17.4(w) x 6.3(d) x 1.7(h) in. (44.2 x 16 x 4.32 cm) (1U height) | 8.27(w) x 8.27(d) x 1.72(h) in. (21 x 21 x 4.36 cm) (1U height) |
| Weight | 6.8 lb (3.08 kg) | 6.8 lb (3.08 kg) | 4.41 lb (2 kg) |
| Memory and processor | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) |
| Performance | | | |
| 100 Mb Latency | < 5 μ s | < 5 μ s | < 5 μ s |
| 1000 Mb Latency | < 5 μ s | < 5 μ s | < 5 μ s |
| Throughput | up to 41.7 Mpps (64-byte packets) | up to 29.8 Mpps (64-byte packets) | up to 13.4 Mpps (64-byte packets) |
| Routing/Switching capacity | 56 Gbps | 40 Gbps | 18 Gbps |
| Routing table size | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) |
| MAC address table size | 8192 entries | 8192 entries | 8192 entries |
| Environment | | | |
| Operating temperature | 32°F to 113°F (0°C to 45°C) | 32°F to 113°F (0°C to 45°C) | 32°F to 113°F (0°C to 45°C) |
| Operating relative humidity | 10% to 90%, noncondensing | 10% to 90%, noncondensing | 10% to 90%, noncondensing |
| Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) |
| Non-operating/Storage relative humidity | 10% to 95%, noncondensing | 10% to 95%, noncondensing | 10% to 95%, noncondensing |
| Acoustic | Pressure: 44.4 dB; ISO 7779 | Pressure: 43.8 dB; ISO 7779 | Pressure: 0 dB No Fan |

| | HP 1910-24G Switch (JE006A) | HP 1910-16G Switch (JE005A) | HP 1910-8G Switch (JG348A) |
|-----------------------------------|---|---|---|
| Electrical characteristics | | | |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| AC voltage | 100–240 VAC | 100–240 VAC | 100–240 VAC |
| Maximum power rating | 31.5 W | 25.1 W | 25.1 W |
| Notes | | | |
| | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | | | |
| | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 |
| Emissions | | | |
| | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Management | | | |
| | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB |
| Notes | | | |
| | SFP ports and copper ports can work simultaneously, independent of each other, to provide a total of 28 Gigabit Ethernet-capable ports. | SFP ports and copper ports can work simultaneously, independent of each other, to provide a total of 20 Gigabit Ethernet-capable ports. | SFP port and copper ports work simultaneously, independent of each other, to provide a total of 9 Gigabit Ethernet-capable ports. |

| | HP 1910-24G Switch (JE006A) | HP 1910-16G Switch (JE005A) | HP 1910-8G Switch (JG348A) |
|-----------------|---|---|---|
| Services | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 24x7 SW phone support, software updates (UV791E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW491E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW492E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW493E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (UOQ25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (UOQ26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW485E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UW488E)</p> <p>Installation with minimum configuration, system-based pricing (UW451E)</p> <p>Installation with minimum configuration, system-based pricing (UY901E)</p> <p>Installation with HP-provided configuration, system-based pricing (UY902E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UV787E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW486E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW489E)</p> <p>4-year, 24x7 SW phone support, software updates (UV790E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UV788E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UW487E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW490E)</p> <p>5-year, 24x7 SW phone support, software updates (UV791E)</p> <p>3 Yr 6 hr Call-to-Repair Onsite (UW491E)</p> <p>4 Yr 6 hr Call-to-Repair Onsite (UW492E)</p> <p>5 Yr 6 hr Call-to-Repair Onsite (UW493E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (UOQ25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (UOQ26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (UOQ25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (UOQ26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> |

HP 1910 Switch Series

Specifications (continued)



| | HP 1910-8G-PoE+ (65W) Switch (JG349A) | HP 1910-8G-PoE+ (180W) Switch (JG350A) | HP 1910-24 Switch (JG538A) |
|---|---|---|---|
| I/O ports and slots | 8 RJ-45 auto-negotiating 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE, IEEE 802.3at) | 8 RJ-45 auto-negotiating 10/100/1000 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T, IEEE 802.3af PoE, IEEE 802.3at) | 24 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full |
| | 1 SFP 1000 Mbps port | 1 SFP 1000 Mbps port | 2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T) |
| | 1 RJ-45 console port to access limited CLI port | 1 RJ-45 console port to access limited CLI port | 1 RJ-45 console port to access limited CLI port |
| | Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination | Supports a maximum of 8 autosensing 10/100/1000 ports plus 1 1000BASE-X SFP ports, or a combination | Supports a maximum of 24 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, with optional module |
| Physical characteristics | | | |
| Dimensions | 10.24(w) x 11.81(d) x 1.72(h) in. (26 x 30 x 4.36 cm) (1U height) | 10.24(w) x 11.81(d) x 1.72(h) in. (26 x 30 x 4.36 cm) (1U height) | 17.32(w) x 6.81(d) x 1.73(h) in. (44 x 17.3 x 4.4 cm) (1U height) |
| Weight | 6.61 lb (3 kg) | 6.61 lb (3 kg) | 4.85 lb (2.2 kg) |
| Memory and processor | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | ARM @ 333 MHz, 128 MB flash, 128 MB RAM; packet buffer size: 512 KB | MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) |
| Performance | | | |
| 100 Mb Latency | < 5 μ s | < 5 μ s | < 5 μ s |
| 1000 Mb Latency | < 5 μ s | < 5 μ s | < 5 μ s |
| Throughput | up to 13.4 Mpps (64-byte packets) | up to 13.4 Mpps (64-byte packets) | up to 6.6 Mpps (64-byte packets) |
| Routing/Switching capacity | 18 Gbps | 18 Gbps | 8.8 Gbps |
| Routing table size | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) |
| MAC address table size | 8192 entries | 8192 entries | 8192 entries |
| Environment | | | |
| Operating temperature | 32°F to 113°F (0°C to 45°C) | 32°F to 113°F (0°C to 45°C) | 32°F to 104°F (0°C to 40°C) |
| Operating relative humidity | 10% to 90%, noncondensing | 10% to 90%, noncondensing | 10% to 90%, noncondensing |
| Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) |
| Non-operating/Storage relative humidity | 10% to 95%, noncondensing | 10% to 95%, noncondensing | 10% to 95%, noncondensing |
| Acoustic | Pressure: 0 dB No Fan | Pressure: 48.6 dB; ISO 7779 | Pressure: 0 dB No Fan |

| | HP 1910-8G-PoE+ (65W) Switch (JG349A) | HP 1910-8G-PoE+ (180W) Switch (JG350A) | HP 1910-24 Switch (JG538A) |
|-----------------------------------|--|--|--|
| Electrical characteristics | | | |
| Frequency | 50/60 Hz | 50/60 Hz | 50/60 Hz |
| AC voltage | 100–240 VAC | 100–240 VAC | 100–240 VAC |
| Maximum power rating | 93 W | 228 W | 12 W |
| PoE power | 65 W | 180 W | |
| Notes | | | |
| | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | | | |
| | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | UL 60950; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03 | IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition |
| Emissions | | | |
| | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Management | | | |
| | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB |
| Notes | | | |
| | SFP port and copper ports work simultaneously, independent of each other, to provide a total of 9 Gigabit Ethernet-capable ports. | SFP port and copper ports work simultaneously, independent of each other, to provide a total of 9 Gigabit Ethernet-capable ports. | |
| Services | | | |
| | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E) 1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E) Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E) 1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E) Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E) 1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E) Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |

HP 1910 Switch Series

Specifications (continued)



| | HP 1910-8 Switch (JG536A) | HP 1910-48 Switch (JG540A) |
|---|---|---|
| I/O ports and slots | <p>8 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T)</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 8 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination</p> | <p>48 RJ-45 autosensing 10/100 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full</p> <p>2 SFP 1000 Mbps ports</p> <p>2 RJ-45 autosensing 10/100/1000 ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3ab Type 1000BASE-T); Duplex: 10BASE-T/100BASE-TX: half or full; 1000BASE-T: full only</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 48 autosensing 10/100 ports plus 2 1000BASE-X SFP ports plus 2 autosensing 10/100/1000 ports, or a combination</p> |
| Physical characteristics | | |
| Dimensions | 10.47(w) x 6.38(d) x 1.73(h) in. (26.6 x 16.2 x 4.4 cm) (1U height) | 17.32(w) x 6.81(d) x 1.73(h) in. (44 x 17.3 x 4.4 cm) (1U height) |
| Weight | 2.2 lb (1 kg) | 5.07 lb (2.3 kg) |
| Memory and processor | MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB | MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 1.5 MB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) |
| Performance | | |
| 100 Mb Latency | < 5 μ s | < 5 μ s |
| 1000 Mb Latency | < 5 μ s | < 5 μ s |
| Throughput | up to 4.2 Mpps (64-byte packets) | up to 13.1 Mpps (64-byte packets) |
| Routing/Switching capacity | 5.6 Gbps | 17.6 Gbps |
| Routing table size | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) |
| MAC address table size | 8192 entries | 8192 entries |
| Environment | | |
| Operating temperature | 32°F to 104°F (0°C to 40°C) | 32°F to 104°F (0°C to 40°C) |
| Operating relative humidity | 10% to 90%, noncondensing | 10% to 90%, noncondensing |
| Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) |
| Non-operating/Storage relative humidity | 10% to 95%, noncondensing | 10% to 95%, noncondensing |
| Acoustic | Pressure: 0 dB No Fan | Pressure: 0 dB No Fan |

| | HP 1910-8 Switch (JG536A) | HP 1910-48 Switch (JG540A) |
|-----------------------------------|---|---|
| Electrical characteristics | | |
| Frequency | 50/60 Hz | 50/60 Hz |
| AC voltage | 100–240 VAC | 100–240 VAC |
| Maximum power rating | 8 W | 22 W |
| | Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. |
| Safety | IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition | IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition |
| Emissions | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Management | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB |
| Services | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> | <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E)</p> <p>1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E)</p> <p>1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E)</p> <p>1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E)</p> <p>1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E)</p> <p>1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p> |

HP 1910 Switch Series

Specifications (continued)



| | HP 1910-8-PoE+ Switch (JG537A) | HP 1910-24-PoE+ Switch (JG539A) |
|---|---|---|
| I/O ports and slots | <p>8 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full</p> <p>2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T)</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 8 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination</p> | <p>24 RJ-45 autosensing 10/100 PoE+ ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX, IEEE 802.3at PoE+); Duplex: half or full</p> <p>2 SFP dual-personality 1000 Mbps ports (IEEE 802.3ab Type 1000BASE-T)</p> <p>1 RJ-45 console port to access limited CLI port</p> <p>Supports a maximum of 24 autosensing 10/100 ports plus 2 1000BASE-X SFP ports, or a combination</p> |
| Physical characteristics | | |
| Dimensions | 12.99(w) x 9.06(d) x 1.73(h) in. (33 x 23 x 4.4 cm) (1U height) | 17.32(w) x 9.37(d) x 1.73(h) in. (44 x 23.8 x 4.4 cm) (1U height) |
| Weight | 4.63 lb (2.1 kg) | 7.28 lb (3.3 kg) |
| Memory and processor | MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB | MIPS @ 500 MHz, 32 MB flash, 128 MB RAM; packet buffer size: 512 KB |
| Mounting and enclosure | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) | Mounts in an EIA standard 19-inch Telco rack or equipment cabinet (hardware included) |
| Performance | | |
| 100 Mb Latency | < 5 μ s | < 5 μ s |
| 1000 Mb Latency | < 5 μ s | < 5 μ s |
| Throughput | up to 4.2 Mpps (64-byte packets) | up to 6.6 Mpps (64-byte packets) |
| Routing/Switching capacity | 5.6 Gbps | 8.8 Gbps |
| Routing table size | 32 entries (IPv4), 32 entries (IPv6) | 32 entries (IPv4), 32 entries (IPv6) |
| MAC address table size | 8192 entries | 8192 entries |
| Environment | | |
| Operating temperature | 32°F to 104°F (0°C to 40°C) | 32°F to 104°F (0°C to 40°C) |
| Operating relative humidity | 10% to 90%, noncondensing | 10% to 90%, noncondensing |
| Non-operating/Storage temperature | -40°F to 158°F (-40°C to 70°C) | -40°F to 158°F (-40°C to 70°C) |
| Non-operating/Storage relative humidity | 10% to 95%, noncondensing | 10% to 95%, noncondensing |
| Acoustic | Pressure: 0 dB No Fan | Pressure: 51.3 dB; ISO 7779 |

| | HP 1910-8-PoE+ Switch (JG537A) | HP 1910-24-PoE+ Switch (JG539A) |
|-----------------------------------|--|--|
| Electrical characteristics | | |
| Frequency | 50/60 Hz | 50/60 Hz |
| AC voltage | 100–240 VAC | 100–240 VAC |
| Maximum power rating | 90 W | 220 W |
| PoE power | 62 W | 180 W |
| | Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). | Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated. PoE power is the power supplied by the internal power supply. It is dependent on the type and quantity of power supplies and may be supplemented with the use of an external power supply (EPS). |
| Safety | IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition | IEC 60950-1; EN 60950-1; UL 60950-1 2nd Edition; CSA C22.2 No. 60950-1-07 2nd Edition |
| Emissions | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A | FCC part 15 Class A; VCCI Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; EN 61000-3-2 2000, 61000-3-3; ICES-003 Class A |
| Management | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB | IMC—Intelligent Management Center; limited command-line interface; Web browser; SNMP Manager; IEEE 802.3 Ethernet MIB |
| Services | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E) 1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E) Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. | 3-year, 4-hour onsite, 13x5 coverage for hardware (UV786E) 1-year, 4-hour onsite, 13x5 coverage for hardware (HR682E) 1-year, 4-hour onsite, 24x7 coverage for hardware (HR683E) 1-year, 6-hour Call-To-Repair Onsite for hardware (HR686E) 1-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support and software updates (HR684E) 1-year, 24x7 software phone support, software updates + Next Business Day Hardware Exchange (U0Q25E) 1-year, 24x7 software phone support, software updates + 4-hour hardware exchange (U0Q26E) Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office. |

Standards and Protocols

(applies to all products in series)

Device management

RFC 2819 RMON

General protocolsIEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s (MSTP)IEEE 802.1w Rapid Reconfiguration of
Spanning Tree
IEEE 802.3 Type 10BASE-T
IEEE 802.3ab 1000BASE-T
IEEE 802.3ad Link Aggregation Control
Protocol (LACP)IEEE 802.3i 10BASE-T
IEEE 802.3x Flow Control
IEEE 802.3z 1000BASE-X**MIBs**RFC 1213 MIB II
RFC 1493 Bridge MIB
RFC 2021 RMONv2 MIB
RFC 2233 Interface MIB
RFC 2233 Interfaces MIB
RFC 2571 SNMP Framework MIB
RFC 2572 SNMP-MPD MIBRFC 2573 SNMP-Notification MIB
RFC 2573 SNMP-Target MIB
RFC 2613 SMON MIB
RFC 2618 RADIUS Client MIB
RFC 2620 RADIUS Accounting MIB
RFC 2665 Ethernet-Like-MIB
RFC 2667 IP Tunnel MIBRFC 2668 802.3 MAU MIB
RFC 2674 802.1p and
IEEE 802.1Q Bridge MIB
RFC 2737 Entity MIB (Version 2)
RFC 3414 SNMP-User based-SM MIB
RFC 3415 SNMP-View based-ACM MIB
RFC 3418 MIB for SNMPv3**Network management**IEEE 802.1AB Link Layer Discovery
Protocol (LLDP)

IEEE 802.1D (STP)

RFC 1215 SNMP Generic traps

QoS/CoS

IEEE 802.1p (CoS)

SecurityIEEE 802.1X Port Based Network Access
Control

HP 1910 Switch Series accessories

Transceivers

HP X121 1G SFP LC SX Transceiver (J4858C)
HP X121 1G SFP LC LX Transceiver (J4859C)
HP X121 1G SFP RJ45 T Transceiver (J8177C)
HP X120 1G SFP LC SX Transceiver (JD118B)
HP X120 1G SFP LC LX Transceiver (JD119B)
HP X120 1G SFP RJ45 T Transceiver (JD089B)

Cables

HP 0.5 m Multimode OM3 LC/LC Optical Cable (AJ833A)
HP 1 m Multimode OM3 LC/LC Optical Cable (AJ834A)
HP 2 m Multimode OM3 LC/LC Optical Cable (AJ835A)
HP 5 m Multimode OM3 LC/LC Optical Cable (AJ836A)
HP 15 m Multimode OM3 LC/LC Optical Cable (AJ837A)
HP 30 m Multimode OM3 LC/LC Optical Cable (AJ838A)
HP 50 m Multimode OM3 LC/LC Optical Cable (AJ839A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 1m Cable (QK732A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 2m Cable (QK733A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 5m Cable (QK734A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 15m Cable (QK735A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 30m Cable (QK736A)
HP Premier Flex LC/LC Multi-mode OM4 2 fiber 50m Cable (QK737A)

Learn more at
hp.com/networking/smb



Products within this series have achieved sufficient scores in each of the rated criteria to achieve the Miercom Certified Green distinction Award. See the Specifications section of this series for more information.

Sign up for updates
hp.com/go/getupdated



Share with colleagues



Rate this document

© Copyright 2010–2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

ARM is a registered trademark of ARM Limited.

4AA1-7808ENW, February 2015, Rev. 7

